

538,905

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
15 July 2004 (15.07.2004)

PCT

(10) International Publication Number  
**WO 2004/059720 A1**

(51) International Patent Classification<sup>7</sup>: **H01L 21/44**,  
21/48, 21/50, 21/331, 21/30, 21/46

12533 (US). YU, Roy [CN/US]; 18 Hankin Loop, Pough-  
keepsie, NY 12601 (US).

(21) International Application Number:  
PCT/US2002/041181

(74) Agent: **ANDERSON, Jay, H.**; International Business Ma-  
chines Corporation, Dept. 18G, Bldg. 300/482, 2070 Route  
52, Hopewell Junction, NY 12533 (US).

(22) International Filing Date:  
20 December 2002 (20.12.2002)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,  
SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN,  
YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (*for all designated States except US*): **INTER-  
NATIONAL BUSINESS MACHINES CORPORA-  
TION** [US/US]; New Orchard Road, Armonk, NY 10504  
(US).


(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK,

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **POGGE, H., Bern-  
hard** [US/US]; 11 LaDue Road, Hopewell Junction, NY

[Continued on next page]

(54) Title: **THREE-DIMENSIONAL DEVICE FABRICATION METHOD**



(57) Abstract: A method is described for fabricating a three-dimensional integrated device including a plurality of vertically stacked and interconnected wafers. Wafers (1, 2, 3) are bonded together using bonding layers (26, 36) of thermoplastic material such as polyimide; electrical connections are realized by vias (12, 22) in the wafers connected to studs (27, 37). The studs connect to openings (13, 23) having a lateral dimension larger than that of the vias at the front surfaces of the wafers. Furthermore, the vias in the respective wafers need not extend vertically from the front surface to the back surface of the wafers. A conducting body (102), provided in the wafer beneath the device region and extending laterally, may connect the via with the metallized opening (103) in the back surface. Accordingly, the conducting path through the wafer may be led underneath the devices thereof. Additional connections may be made between openings (113) and studs (127) to form vertical heat conduction pathways between the wafers.

WO 2004/059720 A1



TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Declaration under Rule 4.17:**

— *of inventorship (Rule 4.17(iv)) for US only*

**Published:**

— *with international search report*  
— *with amended claims*